

MATERIAL SAFETY DATA SHEET

I. PRODUCT IDENTIFICATION

Name: Knight Premium Pressure Sensitive Adhesive
Description: Latex emulsion adhesive

II. DEPARTMENT OF TRANSPORTATION INFORMATION

SHIPPING NAME: Not Classified. HAZARD CLASS: N/A ID#: N/A

EMERGENCY ONLY CONTACT: CHEM-TEL 1-800-255-3924

III. HMIS (0=Minimal hazard; 4=severe hazard)

Health = 1 Flammability = 1 Reactivity = 0

IV. PRODUCT CONTENT

This product does not contain chemicals subject to the reporting requirements of Section 313 of SARA Title III and 40 CFR 372. All components are on TSCA inventory. This product does not contain asbestos.

V. HAZARDOUS INGREDIENTS

INGREDIENT:	CAS#	PERCENT:	OCCUP. EXPOS. LMT.
-------------	------	----------	--------------------

VI. PHYSICAL DATA

APPEARANCE: Off-white paste. ODOR: Mild. BOILING POINT: Approximately 212°F. MELTING POINT: N/A. % VOLATILE BY WEIGHT (30 MIN @ 275°F): 38.5-40.5%. EVAPORATION RATE: Water. WEIGHT/GALLON (WATER=8.3): 8.76. SOLUBILITY IN WATER: Dispersible. SPECIFIC GRAVITY: 1.05. VOC: 0 g/L calculated at 70°F, SCAQMD. pH: 8.5.

VII. FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (METHOD): >200°F (Setaflash Closed Tester). FLAMMABLE RANGE: LEL: N/A; UEL: N/A. EXTINGUISHING MEDIA Use carbon dioxide, dry chemical or water spray. SPECIAL PROCEDURES: Closed containers in a fire may rupture due to pressure build up; use water to cool containers to prevent this. Protect fire fighters from toxic products of combustion with self-contained breathing apparatus.

VIII. HEALTH HAZARD DATA

PRIMARY ROUTES OF ENTRY: Skin and eyes. EFFECTS OF ACUTE EXPOSURE: SKIN AND EYES: May cause irritation of eyes. May cause irritation to skin. MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: None. FIRST AID PROCEDURES: SKIN AND EYES: Flush eyes with plenty of water. Wash skin with soap and water. INGESTION: Do not induce vomiting. If symptoms persist, refer to physician immediately. Carcinogenicity: NTP, No. IARC Monographs, No. OSHA Regulated: No.

IX. REACTIVITY DATA

STABILITY: Stable. INCOMPATIBILITY: Reacts with strong oxidizing agents. REACTIVITY: Hazardous polymerization will not occur. HAZARDOUS DECOMPOSITION: Carbon monoxide, carbon dioxide and other toxic vapors and gases that are common to thermal degradation of organic compounds.

Knight Premium Pressure Sensitive Adhesive

Prepared 2/09

Knight Premium Flooring
7500 4th Street
Marrero, LA 70072

info@kpflooring.com

Manufactured for Knight by W.W. Henry Company

X. SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Contain spill, preventing it from entering sewer lines or waterways. Use absorbent to assist with the pick up of material. Scrape up product and place into container. Residual of product, while still wet, can be cleaned up with warm soapy water. WASTE DISPOSAL METHOD: Dispose of container and any unused contents in accordance with Federal, State and Local waste disposal regulations. Do not flush unused contents or residue down drains. Do not reuse container.

XI. SAFE HANDLING AND USE INFORMATION

VENTILATION: Use natural cross ventilation. RESPIRATORY PROTECTION: With adequate ventilation, respiratory equipment should not be needed. SKIN AND EYE PROTECTION: During normal end product use; impervious gloves, eye protection and eye wash station may be appropriate.

XII. SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Recommended storage temperature is below 90°F. WORKSITE ENVIRONMENT: Initially there may be a potential adverse impact on indoor air quality within the general work area during installation. Therefore, you should advise the building manager or other appropriate person that; it will be necessary to establish and maintain adequate ventilation of the work area, without causing the entry of contaminants to other parts of the building. Persons who are sensitive to odors and/or chemicals should avoid the work area during this process.

The information presented herein is supplied as a guide to those who handle or use this product. Safe work practices must be employed when working with any materials. It is important that the end user makes a determination regarding the adequacy of the safety procedures employed during the use of this product.